

HIGH TEMP AEC-Q200 INDUCTORS – EF4P4532ELQ1 SERIES




●FEATURE

1. For automobile signal line
2. Same as TDK ACT45B type
3. AEC-Q200 Qualified.(125 degree Grade)

●Applications

1. CAN-BUS, FlexRay etc

●Shape and Dimension and Schematics and Land Patterns(Dimension in m/m)



●Specification

PART NO.	Common Mode Inductance (uH) (+50%/-30%)	Common Mode Impedance(Ω) at 10MHz	Rated Current (mA)	Rated Voltage Withstand Voltage (Vdc)	Insulation Resistance (M ohm)	DC Resistance (max.) (ohm)
EF4P4532ELQ1-110	11uH at 100KHz	300Ω Min. 600Ω typ.	250	50 125	10 min	0.6
EF4P4532ELQ1-220	22uH at 100KHz	500Ω Min. 1200Ω typ.	200	50 125	10 min	1.0
EF4P4532ELQ1-510	51uH at 100KHz	1000Ω Min. 2800Ω typ.	200	50 125	10 min	1.0
EF4P4532ELQ1-101	100uH at 100KHz	2000Ω Min. 5800Ω typ.	150	50 125	10 min	2.0

Note1. Measurement ambient temperature of electrical : at 20°C

Note2. Test equipment: HP4291A

Note3.Packaging: Taping ; Quantity: 500 Pieces/reel




An ISO 9001 Company

HIGH TEMP AEC-Q200 INDUCTORS - EF4P4532ELQ1 SERIES




● EF4P 4532ELQ1 (Impedance VS Frequency)


EF4P4532ELQ1-110




EF4P4532ELQ1-220




EF4P4532ELQ1-510




EF4P4532ELQ1-101



● Test circuit



COMMON MODE



NORMAL MODE

Specifications and dimensions are subject to change.


For the latest product information, please visit our website at www.pacer.com.tw or email us at pacer@mail.ece.com.tw




GENERAL CHARACTERISTICS

1. Operating temperature range: -40 TO + 125°C (Includes temperature when the coil is heated)
2. High temperature exposure(storage) refer MIL-STD-202 Method 108: 1000 hrs at rated operating temperature(e.g. 125°C). Part can be stored for 1000 hrs @125°C. Unpowered. Measurement at 24±4 hours after test conclusion.
3. Temperature cycling refer JESD22 Method JA-104: 1000 cycles(-40 TO + 125°C). Measurement at 24±4 hours after test conclusion. 30 min maximum dwell time at each temp. extreme. 1 min. maximum transition time.
4. Biased Humidity refer MIL-STD-202 Method 103: 1000 hours 85°C/85%RH. Unpowered. Measurement at 24±4 hours after test conclusion.
5. Operational Life refer MIL-PRF-27: 1000 hrs. at 125 °C tested. Measurement at 24±4 hours after test conclusion.
6. External Visual refer MIL-STD-883 Method 2009: Inspect device construction, marking and workmanship.
7. Physical Dimension refer JESD22 Method JB-100: Verify physical dimensions to the applicable device detail specification.
8. Resistance to Solvents refer MIL-STD-202 Method 215: Add aqueous wash chemical - OKEM clean or equivalent.
9. Mechanical Shock refer MIL-STD-202 Method 213: Figure 1 of Method 213. Condition C.
10. Vibration refer MIL-STD-202 Method 204: 5g;s for 20 minutes, 12 cycles each of 3 orientations. Test from 10-2000 Hz.
11. Resistance to soldering Heat refer MIL-STD-202 Method 210: Condition B No pre-heat of samples. Single wave solder-procedure 2 for SMD and procedure 1 for leaded with solder within 1.5mm of device body.
12. ESD refer AEC-Q200-002 or ISO/DIS 10605: Direct contact discharge 2kV.
13. Solderability refer J-STD-002: For both Leaded & SMD. Magnification 50X. Conditions: Leaded, Method A@235°C ,category 3 ; SMD, a)Method B, 4hrs@125°C dry heat @235°C , b)Method B@215°C category 3., c)Method D category 3@260°C
14. Electrical Characterization refer spec: Show Min, Max Mean and Standard deviation at room from Min and Max temperature.
15. Flammability refer UL-94: V-0 or V-1 Acceptable.
16. Board Flex refer AEC-Q200-005: 60 sec minimum holding time.
17. Terminal Strength(SMD) refer AEC-Q200-006
18. Reflow profile recommend:

Lead-free heat endurance test



Lead-free the recommended reflow condition



Specifications and dimensions are subject to change.

For the latest product information, please visit our website at www.pacer.com.tw or email us at pacer@mail.ece.com.tw